

xPortal is in the end-of-life process.

# Impinj Gateway Portfolio



Impinj xArray

Impinj xSpan

Impinj xPortal

	Impinj xArray	Impinj xSpan	Impinj xPortal	
SPECIFICATIONS	Air interface protocol			
	RAIN RFID / ISO 18000-63 and EPCglobal Gen2v2 compliant			
	Deploy	Fixed, overhead	Fixed, overhead or entries/exits	Fixed, entries/exits
	Coverage	≤ 140m <sup>2</sup> (1,500 sq.ft.)	≤ 90m <sup>2</sup> (1,000 sq.ft.)	≤ 65m <sup>2</sup> (700 sq.ft.)
	Read zones	52	13	2
FEATURES	Radiated power (max) <i>Refer to regulations for country-specific limitations</i>	4W EIRP AC/PoE	4W EIRP AC/PoE	4W EIRP AC/PoE
	Turnkey implementation	✓	✓	✓
	Built-in antennas	✓	✓	✓
	Always-on endpoint monitoring	✓	✓	✓
	Endpoint (tagged item) location mapping	✓		
	Threshold monitoring	✓	✓	
Power sources	AC-DC power supply: all models IEEE 802.3af PoE: all models except EU2 IEEE 802.3at PoE+: EU2 model		AC-DC power supply: all models IEEE 802.3af PoE: all models	